



Specification Sheet

Blowout preventor & Accumulator webpage

Introduction

Our BOPs are tested and redressed before each job utilizing top of the line elastomers. All blowout prevention equipment is maintained to API Standard 53 and API 16AR standards from cradle to grave.

Blowout Preventors (“BOP”)

- 11” 10,000 lbs rated hydraulic BOPs
Type U Double
- 7 1/6” 10,000 lbs rated hydraulic BOPs
GK and T90 Annulars, Type U/UM Single, Type U/UM Double with optional shearing packages available.
- 7 1/6” 5,000 lbs rated hydraulic BOPs
GK and T90 Annulars T-81 Single, T-81 Double, Type U/UM Single, Type U/UM Double, with optional shearing packages available.
- 7 1/6” 5,000 lbs rated manual BOPs
T-81 Double



Accumulators

Wildcat’s range of accumulators give you versatility handle your well control stack configuration. Giving you peace of mind that you are operating with best-in-class safety features.

Wildcat offers:

- 6 station 120-gallon accumulators
- 5 station 80-gallon and 60-gallon accumulators
- 4 station 80-gallon and 40-gallon accumulators
- 3 station 40-gallon accumulators
- Optional dual power sources including nitrogen air backups and configurations with two diesel engines complete with auto start.
- Optional remote-control panels

